







CTM-CI-100

4-Post 100 Ton Ceramic Injection Machine*

*Shown without CE Guarding for clarity



QUALITY • PERFORMANCE • RELIABILITY

STANDARD FEATURES

INJECTION SYSTEM

- + Our in-line injection system allows the material to be injected in a smooth straight line from the injection chamber through our unique nozzle design and into the die. This insures a smooth laminar flow that prevents turbulance.
- + Select from three injection control systems suited to the user's needs. All systems contain excellent temperature, pressure, and flow control.
- + Automatic purge of material after each cycle.
- + Automatic material charge between cycles.
- + 5 zones of temperature control.

PRESS

- + Available with work table or shuttle table
- + T-Slots on bottom and moving platen
- + Low oil level alarm/shutdown
- + High temperature alarm/shutdown
- + Ultra quiet pumping system
- + Independent platen cooling

OPERATOR

- + All functions on easy-to-use touch screen interface in user's language
- + Reduced operator fatigue due to ergonomic controls
- + Built to NFPA, ANSI, OSHA, & CE safety standards

WARRANTY

+ All machines have a full 1 year warranty on all materials and worksmanship

CTM C FRAME WAX INJECTION MACHINES ARE DESIGNED TO PRODUCE THE HIGHEST QUALITY PATTERNS

Contact Us Today!

Email: sales@clevtool.com Website: www.clevtool.com

Tel: (216) 267-6010 Fax: (216) 267-6011





CERTIFIE



ABOVE: CTM CI 100, 100 Ton Ceramic Injector

Features: Advanced controls, Shuttle Table, & more *Shown without CE Guarding for clarity

ALL MACHINES ARE AVAILABLE WITH CE SAFETY SYSTEMS
FOR EU COUNTRIES


NOW INCLUDES REMOTE ACCESS!


ASK ABOUT OUR AVAILABLE OPTIONS
TO ENHANCE YOUR MACHINE!



CTM-CI-100

4-Post 100 Ton Ceramic Injector





| CTM-CI-100 Ton Specifications | | |
|--|------------------------------|-------------|
| | Imperial | Metric |
| Clamp Force- Tons | 0-100 Ton | |
| Press Closing Speed | 1.5 in./sec | 38 mm/sec |
| Press Opening Speed | 1.5 in./sec | 38 mm/sec |
| Die Mounting | 1/2 in T-Slots | |
| Water Cooled Platens | Included | |
| Material Holding Tank Capacity | 30 Gal | 114 Liter |
| Shot Size | 462 cu. In | 7.5 Liter |
| Injection Pressure | 0-1000 PSI | 69 BAR |
| Injection Flow Rate Maximum | 25 cu.in/sec | 425 cc/sec |
| Injection Cycle Time | 0-999 sec | |
| Nozzle Tip Size | 3/8 in. radius .95 mm radius | |
| Heating System | 120 volt- 5+ zones | |
| Hydraulic System Pressure | 2900 PSI | 200 BAR |
| Hydraulic Pump Type | Press. Compensated | |
| Hydraulic Reservoir Capacity | 40 Gal | 150 Liter |
| Hydraulic Cooling System | Water Cooled Heat Exchanger | |
| Minimum Cooling Water Flow | 3 GPM | 11 LPM |
| Maximum Cooling Water Temp | 80°F | 27 °C |
| Cooling Water Connection | 1/2 inch NPT | |
| Standard Electric | 460V 3Ph 60 HZ 30 @ | |
| Air Pressure (If Required) | 60-80 PSI | 4.1-5.5 BAR |
| Approximate Weight | 19,000 Lbs | 8700 Kgs |
| A.) Height | 117 in | 3480 mm |
| B.) Length | 110 in | 2790 mm |
| C.) Floor to Table | 36 in | 914 mm |
| D.) Press Opening | 4-36 in | 100-914 mm |
| E. Distance between Tie Bars | 36 in | 914 mm |
| F.) Nozzle In/Out | 0-12 in | 0-305 mm |
| G.) Nozzle Up/Down | 2-12 in | 50-305 mm |
| H.) Width | 90 in | 2286 mm |
| I.) Press Depth | 48 in | 1219 mm |
| J.) Shuttle Table | 50 in | 1290 mm |
| * Special sizes available upon request | | |

^{*}Pictured Duel Wax Tank Optional





ISO 9001:2015

AVAILABLE OPTIONS

- + Electronic Injection Control System
- + Extra Large Color Touch Screen
- + Swing Arm/Pedestal for HMI
- + Data Storage
- + Bar Code Scanner
- + Platen Temperature Control- For heating and cooling
- + PLC Remote Connection
- + Die Transfer Shuttle Table- To move die in and out of press area
- + Increased capacity injection shot sizes
- + Removable Holding Tanks
- + Safety Light Curtains
- + Bottom Injection
- + Pattern Ejection System- Bottom centerline
- + Crane and Hoist
- + Core Pull
- + Remote Injection Nozzle
- + Operator Work Light
- + Water Filtration
- + Temperature Callibration Test Ports
- + Operator Air Gun
- + Magnetic Platens
- + Quick Die Clamping
- + Dual Operator Stations
- + Function/Status Light Towers

ELECTRONIC INJECTION CONTROLS





Contact Us Today!

Email: sales@clevtool.com Website: www.clevtool.com

Tel: (216) 267-6010 Fax: (216) 267-6011



